Spectralink Base Stations used with the Spectralink DECT Server 2500 and 8000

The table below outlines which Spectralink Base Sations that can be used with the Spectralink DECT Server 2500 and 8000 and the features they support. Spectralink recommends usage of RFP5/RFP6 Base Stations in all installations.

Please note, that when installing your Spectralink DECT Server 2500 and 8000 system, it is recommended to turn off all other running DECT systems to avoid any disturbance. Moreover, all handsets must be upgraded to latest SW version. For easy software upgrade of your handsets use the Spectralink 7000 Series Software Updater.

Spectralink Base Station	Software Part Number	Software version	Connectes with Spectralink Server	Broadcasting	Central updates via server	Detection of alien base stations
RFP 2						
RFP 3 *	14024501		Х			
RFP 4 **	14024530	Lowest PCS 4x - Highest PCS 6x	х			
PRF 4 **	14024502	Lowest PCS 8x - Highest PCS 11x	х	х	x (PCS9 or newer)	
RFP 5	14170201		х	х	х	Х
RFP6 - 4 Channel	14217700		х	х	х	Х
RFP6 - 8 Channels	14217710		х	х	х	Х
KIRK IP Base Station	14128100		х	х	х	Х
Spectralink IP-DECT Base Station	14218500		х	х	х	х

Notes:

x = supported



^{* =} Spectralink recommends an upgrade to RFP5

^{** =} Spectralink recommends an upgrade to latest software version