

Spectralink 7000 Portfolio Application Reference Guide

	Application Protocol	Message Service Functions (MSF) Support	Interface	Voice	Int./Ext. ringing	MWI	Internal messaging with callback number (1)	Simple text messaging (2)	Text calls (3)	Advanced messaging (3)	Broadcast messaging	Receive status events from endpoints (5)	Alarm button	LED control	Multi-color LED control	Tear-off detection	Man-down detection	No movement detection	Running detection	Color icons	Task lists (6)
				Call control			MSF I			MSF II			MSF III								
Third-party controlled application								X	X	X	X	X	X	X	X	X	X	X	X	X	X
GAP Handset				X	X	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Spectralink Butterfly Handset		MSF I+II		X	X	X	X	X	X	X	X	X	-	-	-	-	-	-	-	-	
Spectralink 7420 Handset		MSF I + II		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	-	-	
Spectralink 7440 Handset		MSF I + II		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	-	-	
Spectralink 7280 Handset		MSF I + II		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	-	-	
Spectralink 7520 Handset		MSF I + II		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	-	-	
Spectralink 7540 Handset		MSF I + II		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	-	-	
Spectralink 7620 Handset		MSF I + II + III		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	X	X	
Spectralink 7640 Handset		MSF I + II + III		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Spectralink 7710 Handset		MSF I + II + III		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	X	X	
Spectralink 7720 Handset		MSF I + II + III		X	X	X	X	X	X	X	X	X	X	X	-	-	-	-	X	X	
Spectralink 7740 Handset		MSF I + II + III		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Spectralink IP-DECT Server 400	MSF-DLL, XML-RPC	MSF I + II + III	IP	X	X	X	X	X	X	X	X	X	X	X	X*	X*	X*	X*	X*	X*	
Spectralink DECT Server 2500	SIO 2, XML-RPC	MSF I + II + III	IP + RS232	X	X	-	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Spectralink IP-DECT Server 6500	MSF-DLL, XML-RPC	MSF I + II + III	IP	X	X	X	X	X	X	X	X	X	X	X	X*	X*	X*	X*	X*	X*	
Spectralink IP-DECT Server 8000	SIO 2, XML-RPC	MSF I + II + III	IP + RS232	X	X	-	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
KIRK Wireless Server 300**	MSF-DLL, XML-RPC	MSF I + II + III	IP	X	X	X	X	X	X	X	X	X	X	X	X*	X*	X*	X*	X*	X*	
KIRK Wireless Server 6000**	MSF-DLL, XML-RPC	MSF I + II + III	IP	X	X	X	X	X	X	X	X	X	X	X	X*	X*	X*	X*	X*	X*	

Notes

*) Only supported by XML-RPC

**) This product has reached End Of Life (EOL)

1) MSF message with callback number. Always internally directly to the handset

2) MSF message sent to the API PC, which will redirect. E.g. the machinery is sending the messages

3) Interactive remote menu such as corporate phone book in the KIRK Wireless Server 6000 or stock management (looking for item numbers, prices etc.)

4) Callback number, Alert type control, Vibration control, and Save in Stack control

5) In/Out of charger, low battery warning, or battery status etc.

6) Send task to a predefined group. When one person accepts, the task is deleted from the other handsets

X = supported

- = not supported

