

Yealink MeetingBar A25 Datasheet

All-in-One Android Video Collaboration Bar for Focus Rooms

Yealink MeetingBar A25 is an all-in-one video collaboration bar for focus rooms. It is equipped with an advanced triple-camera system and offers a 151° ultra-wide field of view and a high-definition image. It also integrates a high-quality loudspeaker and an 8x MEMS microphone array. Its built-in intelligent noise reduction technology delivers a superior audio experience for meetings

Yealink MeetingBar A25 is built on the Android 13 operating system and will continue to receive future upgrades, ensuring users have access to the latest features and enhancements. In addition, it is compatible with Microsoft's MDEP, which enhances security and deployment experiences. This integration provides users with a more secure environment and streamlined deployment processes, contributing to a smoother and safer user experience. Moreover, Yealink MeetingBar A25 features a direct connection to CTP25, enabling a simplified login process. This streamlined login experience saves users time and enhances convenience.



Key Features and Benefits

- An advanced triple-camera system
- High-quality audio pickup experience



- Compatible with Microsoft's MDEP
- Multi-Platform Flexibility
- Simple deployment
- Remote device management

An advanced triple-camera system

The advanced triple-camera system achieves a 151° ultra-wide field of view, enabling capture of all attendees in Focus Rooms. At the same time, it provides high-definition portrait close-ups, capturing every detail of interaction and enhancing the meeting viewing experience for remote participants.

High-quality audio pickup experience

The Yealink MeetingBar A25 features a 5-meter voice pickup range, integrating a high-quality loudspeaker, 3-meter full-duplex technology, and an 8x MEMS microphone array, which delivers exceptional sound playback and voice pickup performance. Its built-in intelligent noise reduction technology ensures a superior audio experience for meetings.

Compatible with Microsoft's MDEP

Yealink MeetingBar A25 is compatible with Microsoft's MDEP, which enhances security and deployment experiences. This integration provides users with a more secure environment and streamlined deployment processes, ultimately enhancing the overall user experience.

Simple deployment

Yealink MeetingBar A25 features a direct connection to CTP25, enabling a simplified login process. Only need to log in once. This streamlined login experience saves users time and enhances convenience.

Multi-Platform Flexibility

Yealink MeetingBar A25 supports native Teams Rooms, Zoom Rooms, etc. Additionally, it supports BYOD*. In BYOD mode, MeetingBar A25 can serve as video and audio peripherals for your computer in meetings via third-party applications.

Remote Device Management

The Yealink MeetingBar A25 is networked and reports to the device management platform,



allowing for remote management, configuration, and upgrades.

Specifications

Parameter	Description			
Operating System	• Android 13			
	Based on Microsoft Device Ecosystem Platform (MDEP)			
Camera	Number of cameras: 3			
	• Lens FOV			
	- 1x Ultra-Wide Camera: DFOV 182°, HFOV 151°, VFOV 81°			
	- 2x Tele Camera: DFOV 93.5°, HFOV 84.4°, VFOV 53.1°			
	• Maximum pixels: 3 * 4k Cameras, all with 8MP image sensors			
	Number of preset positions: 9			
	• Depth of field: 0.4-2.5 meters			
	Maximum resolution: 3840 * 2160			
	Maximum frame rate: 30fps			
	• Video output resolution: 4k (2160p) 30fps, 1080p60fps			
	Privacy cover: Electric lens cap			
	Electronic gimbal			
	• Lens calibration			
	Intelligence Features			
	- IntelliFocus (2 portraits)			
	- Auto Framing			
	- Speaker Tracking			
	- Picture in Picture			
	- Video Fence			
	- Smart Gallery (Zoom Rooms only)			
Speaker	Built-in a 10W speaker			
	- Rated power: 10W			
	- Maximum power: 12W			
	Maximum sound pressure level: 90dBSPL 10W@1m			
	• Frequency response: 100-16kHz			
	Sensitivity: 86dB SPL @ 1W @ 0.5 meter			
	Sampling rate: 48kHz			
	Sound emission angle: Forward-facing			



	• Total Harmonic Distortion (THD): at 10W, 1kHz, <5%			
	Rated impedance: 4 ohms			
Microphone	Built-in 8 MEMS microphone array			
	• 5-meter pickup distance, 3.5-meter high-quality pickup distance			
	Signal-to-noise ratio: 72dB@1kHz			
	Maximum sound pressure level: 130dBSPL (whole device),			
	100dBSPL (individual microphone)			
	Dynamic range: 28-100dBSPL			
	Sensitivity: -38dBV/pa			
	Frequency response: 100-20kHz			
	Sampling rate: 48k32bit			
	Bit depth: 32-bit			
	Audio processing: Full duplex, AEC (Acoustic Echo Cancellation),			
	AGC (Automatic Gain Control)			
	Noise suppression: Al-enhanced noise suppression			
	Expansion Mics: not supported			
Resolution	• Lens Resolution: up to 4k30fps			
	Bandwidth requirement: 10Mbps or more			
Content sharing	• Teams: 1080P30fps in meeting, 4k30fps in local sharing			
	• Zoom: up to 1080p30fps			
	General Mode (BYOM): up to 4k30fps			
	RingCentral: 1080p30fps			
	• H.323/SIP: 1080p30fps			
Video Codec	• H.264 High profile, H.264 SVC, H.264			
Audio Codec	ARES: 24kHz bandwidth			
	• G.722.1C: 16kHz bandwidth			
	• G.722.1: 8kHz bandwidth			
	• G.722: 8kHz bandwidth			
	• G.711 (PCMA/PCMU): 4kHz bandwidth			
	• G.729: 8kHz bandwidth			
Security	• Full Disk Encryption: AES-128, AES-256			
	Data Encryption: Symmetric Keys, PKI			
	Device Identity: Protected by device attestation			



	Device Access: Authenticated using API				
	Key Protection: Arm TrustZone, RPMP				
Communication	• H.323/SIP in General Mode				
standard protocol	• Dual stream protocol: H.239 (H.323) / BFCP (SIP)				
	• FECC: H.224/H.281				
	• H.323 protocol suit: H.245, H.225, H.235, H.241				
	Gatekeeper account and SIP account				
Network Protocol	• Wi-Fi 6				
	- 2.4G & 5G dual-band, 802.11a/b/g/n/ac/ax				
	- 2x2 MIMO				
	• Bluetooth 5.1				
	• TCP/IP (IPv4/IPv6), DHCP/static IP				
	HTTPS secure web access				
Configuration	Automatic configuration via web page/display/AutoP				
Management	Firmware upgrade, factory reset				
	Configuration import and export				
	System log export				
Device	Yealink Https Web Portal				
Management	Yealink Device Management Platform				
	Yealink Management Cloud Service				
	Microsoft Device Management Platform(Microsoft Teams Admin				
	Center/Intune)				
	Zoom Device Management				
Installation	Wall mount (provided with the product)				
	Use TV Mount (additional: purchase VB-TVMount-01, VB-				
	TVMount-02 or TV-Clip Mount)				
	• Place on the desktop (additional: purchase VB-TabletopMount-01)				
Ports	• 1x USB2.0 Type-A port				
	• 1x USB2.0 Type-C port (side)				
	• 1xUSB3.0 Type-C port				
	- video input supports formats up to maximum 4k30 fps, including				
	1080p60fps				
	• 1x Ethernet port: 10/100/1000Mbps				



	1		
	• 1x Yealink VCH port (RJ-45)		
	• 1x HDMI-out port		
	- video output supports formats up to maximum 4k30fps, including		
	1080p60fps		
	- supports HDMI CEC		
	• 1x 3.5mm Line-out port		
	• 1x Power port		
	• 1x Security lock slot		
	• 1x Reset slot		
Package	MeetingBar A25		
	• Power adapter, 3.5m/11.48ft		
	• 1x HDMI cable, 1.8m/5.91ft		
	• 1x Network cable, 3m/9.84ft		
	• 1x USB A to C cable, 3.0m/9.84ft		
	• Wall Mount		
	• Cable cover		
	MeetingBar A25 quick start guide		
	Optional Package		
	- A25-010: A25+VCR11+USB C to C cable (1.8m/5.91ft)		
	- A25-031: A25+CTP25 Package (CTP25, 2m/6.56ft 65W PD power		
	adapter, 7.5m/24.6ft Network cable, 1.2m/3.94ft USB C to C cable,		
	High stand, Cable management cover)		
Environmental	Operating humidity: 10 - 95%		
Factor	Operating temperature: 0 - 40°C		
	• Storage temperature: -30°C~70°C		
	• BTU/hr: 38 in idle, 58 in meeting		
Dimensions and	MeetingBar A25: 570x80x65 mm		
weight(W \times D \times H)	• N.W/CTN: 3.812kg		
	• G.W/CTN: 4.290kg		
Warranty	Standard: 2-year limited hardware warranty included		
	Extended: Additional extended warranties are available at the		
	time of hardware purchase. Contact your reseller.		



MeetingBar Kit

Meeting Room	Mode	Kit Contain	Related
Туре	l		Topic
Focus & Huddle Room	A25-0 10	MeetingBar A25+USB C to C cable+VCR11	MeetingBar A25
Focus & Huddle	A25-0	MeetingBar A25+CTP25	MeetingBar
Room	31		<u>A25</u>