

DHI-LM75-V400

75" UHD Monitor



Features:

- High fidelity digital processing for a brilliant and vivid video;
- Professional thermal design to extend equipment lifespan;
- Ultra-high brightness
- Adopting a high-temperature resistant LCD screen

Precautions:

To ensure the normal operation of this product, please confirm that the distance between the LCD screen and the window is greater than 200mm

Technical Specification

Model

Model	DHI-LM75-V400
-------	---------------

Display

Screen Size	75"
Panel type	IPS
Aspect Ratio	16 : 9
Resolution	3840 x 2160
Backlight	LED
Brightness/Luminance	3000 cd/m ² (max)
Contrast	1200 : 1
Display Color	1.07B
Viewing Angle(H/V)	178° (H)/178° (V)
Display Mode	Horizontal/ Vertical
Response time(typ.)	8 ms
Refresh Rate	60 Hz

Signals

Input	HDMI x 2 , VGA x 1, CVBS x 1, DVI x 1, USB x 1
Output	RS232 IN x 1, RS232 OUT x1
Speaker	2 x 5 W (8 Ω)

General

Power Supply	220 VAC, 60 Hz	
Consumption (Max)	680 W	
Consumption (Standby)	< 0.5 W	
Automatic brightness adjustment	Yes	
Net Weight	50 kg (110.23 lb)	
Gross Weight	85 kg (187.39 lb)	
Bezel Width	18 mm (0.71") (U/R/L/B)	
Wall Mount	400 mm x 400 mm (15.7" x 15.7")	
Horizontal and vertical installation	Yes	
Dimension without stand	1689.6 mmx 968 mm x 85 mm (66.5"x 38.1"x 3.3") (Lx H x W)	
Package	1855 mmx 1140 mmx 260 mm (73" x 44.9" x 10.2") (Lx H x W)	
Work Environment	Temperature	-20°C~+45 °C (-4°F ~113°F)
	Humidity	10% ~ 85% (RH)

Accessory

Standard	power cable, Screws, Remote Control
----------	-------------------------------------

Certifications

Certifications	CE- EMC, CE-LVD, CE-ERP
----------------	-------------------------

Dimensions(mm)

