

DHI-PHSIA1.2-CH Indoor Fine Pixel Pitch LED



Features :

- · Mini COB(Chips on Board) technology.
- · Ultra-thin 39mm and super-light 4.0kg design.
- 16:9 Golden aspect ratio , can easily achieve pixel to pixel 2K,4K,8K,16K resolution.
- \cdot CNC die-casting aluminum cabinet, splicing tolerance is controlled within ±0.1mm.
- · All parts support front maintenance.

 \cdot Dot by dot calibration ensures color richness and brightness uniformity.



Technical Specification Model DHI-PHSIA1.2-CH Model Operating Temperature/ -10 C~+40 C/10~80%RH Parameters Humidity Storage Temperature/ Pixel Pitch 1 25mm -20 °C~+60 °C/10~80%RH Humidity Pixel Configuration 1R1G1B Front IP65/Rear IP43 IP Rating LED Type Flip COB Chip Aspect Ratio 16:9 Brightness (Max) 800 nit 12-14 bit Gray Scale Color Temperature 9300K ± 200K Contrast Ratio 10000:1 H160°/V160° Refresh Rate 3840Hz Viewing Angle AC 100~220V (+/-10%) Pixel Density 640,000 dots/m² Input Voltage Input Power (max) 350 W/m² Module Size 150mm×168.75mm 120 W/m² Module Resolution Input Power (Avg) 120x135 dots W600mm×H337.5mm×D39.5mm Installation Wall Mounted/Floor Mounted Cabinet Size Maintenance Front Maintenance Cabinet Resolution (W×H) 480×270 dots ≥100.000 H Lamp Lifespan Cabinet Weight 4.0 kg ± 0.1 CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), Cabinet Material Die-casting Aluminum Signal Transmission Distance single mode fiber (L≤10km)

Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.