

SIP-T87W

Ultra Prime Business Phone to Deliver Optimum Desktop Productivity

Especially designed for busy executives and professionals, the Yealink SIP-T87W is an intuitive Prime Business Phone with a 7-inch multi-point touch screen. It allows you to easily find a comfortable viewing angle and provides effortless navigation with just one touch. The SIP-T87W delivers ultra-high-definition sound quality and supports broadband audio codecs for realistic call effects. Yealink's self-developed AI noise cancellation ensures superior audio quality during calls. With built-in Bluetooth 5.0 and dual-band 2.4G/5G Wi-Fi 6 modules, it keeps you updated with the latest technology, ready for the future wireless era. The T8X series enhances the Yealink ecosystem, supporting more Yealink headsets. It allows headset configuration and upgrades via the LCD and works with headsets featuring a wearing detection function for intelligent channel switching.

* Only BH76 supports intelligent channel switching.





















Multitouch

Adjustable Corded-Cordless Screen Phone

Sharing

HD Audio

Built-in Built-in Bluetooth

Wi-Fi

USB 20

Key Features and Benefits

- Linux 6.1 version
- TEE hardware encryption solution
- Dual system function
- T7X and T8X firmware unified
- Up to 16 SIP accounts
- PoE support
- Support USB headset and EHS
- Built-in Bluetooth, WiFi
- Supports color-screen expansion modules
- Two adjustable angles for desktop placement
- Wall mountable
- Handset with hall switch

Outstanding user experience

T87W IP Phone features an adjustable 7-inch capacitive touch screen that you can readily adjust to a comfortable viewing angle according to yourself. In addition, a clearly defined set of menus is easy to navigate when all you



have to do is touch the desired option, ensuring you have an optimized interface for a smartphone-like user experience.

HD audio

Regarding audio quality, the T87W features Yealink Optimal HD Voice technologies, including Acoustic Shield technology, which effectively eliminates background noise and delivers crystal-clear voice even in noisy environments. Yealink's AI noise cancellation further enhances audio quality during calls. Additionally, its HAC handset complies with Hearing Aid Compatibility (HAC) regulations, helping those with hearing loss hear more clearly.

High security and compatibility

T87W adopts the latest network security technology, supports SRTP and TLS call encryption, 802.1x media access control, MD5 and MD5-Sess based authentication, AES security profile, and other perfect security protection mechanisms to avoid hacker attacks. Widely compatible with third-party SIP devices and leading SIP platforms. In addition, T87W supports a dual system function, which can back up your phone system in advance to avoid system crashes caused by upgrade failure, thus providing you with enterprise-level system protection. T7/T8X series also supports a security center function to ensure your phone is more secure. At the same time, high-sensitivity functions and data support user individual control, as well as one-click disconnection.

Customizability and scalability

T87W has its own two USB ports. You can choose any according to your needs. T87W supports five pages of page turning and can support up to 60 programmable buttons; in addition, T87W can cascade up to 3 color screen expansion units, expanding 234 programmable buttons to save operation time and achieve efficient office work effectively.

Wireless transmission

T87W has a built-in Bluetooth 5.0 module, supports Bluetooth headsets, and can connect to mobile phones via Bluetooth for phone address book matching. At the same time, to adapt to the upcoming 5G Wi-Fi era, SIP-T87W has built-in dual-band Wi-Fi 6 (Dual band). 5G Wi-Fi has better anti-interference and faster speed, allowing you to be one step ahead in the busy data torrent. In addition, SIP-T87W can be used with the Yealink video conferencing soft terminal to share the content on the computer to the remote end, giving you the ultimate content-sharing experience.

Incorporating Linux 6.1 and TEE hardware encryption solution

The T87W uses the updated Linux 6.1 version, which makes the system more secure and has stronger performance. At the same time, T87W also uses the TEE hardware encryption solution, which can provide you with a more secure data storage experience.

Specifications

Specification	Description
3	



Audio Features	 HD voice: HD handset, HD speaker Hearing aid compatible (HAC) handset Acoustic Shield Smart Noise Filtering Audio codec: AMR-WB (optional), G.722 Narrowband codec: AMR-NB (optional), PCMU (G.711μ), PCMA (G.711A), G.723.1, G.729, G.729A, G.729B, G.729AB, G.726, iLBC DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO Full-duplex hands-free speakerphone with AEC VAD, CNG, AEC, PLC, AJB, AGC
Display and Indicator	 7" 800 x 480 capacitive adjustable touch screen LED for call and message waiting indication Dual-color (red or green) illuminated LEDs for line status information Intuitive user interface with icons and soft keys Multilingual user interface Caller ID with name, number, and photo Wallpaper Screensaver Intelligent power saving Supports both dark and light themes
Phone Features	 16 VoIP accounts One-touch speed dial, hotline, mute, DND Call hold, call forward, call waiting, call transfer Group listening Emergency call Redial, call return, auto answer Direct IP call without SIP proxy Ring tone selection/import/delete Set date time manually or automatically Dial plan, XML Browser, action URL/URI RTCP-XR XML Browser, XML Push Custom DSS Key Accessibility features
Directory	 Local phonebook up to 1000 entries Blocklist XML/LDAP remote phonebook Smart dialing Phonebook search/import/export Call history: all records/dialed/received/missed/forwarded



IP-PBX Features	 Busy Lamp Field (BLF), Bridged Line Appearance (BLA) Anonymous call, anonymous call rejection Message Waiting Indicator (MWI) Voice messages, call parking Call pickup, intercom, multicast Music on hold Call recording, mobile office, chief assistant Server-based recording function Visual mailbox user interface
Feature keys	 84 one-touch DSS keys 4 function keys: call hold, call transfer, redial, hands-free 2 volume adjustment buttons 6 navigation keys
Interface	 Dual-port Gigabit Ethernet 2 x USB port (Type-USB A, Type-USB C) USB flash drive Connecting a USB headset Connecting to the color screen expansion station Wireless Headset Adapter EHS40 1 x Security keyhole 1 x RJ9 (4P4C) handset port 1 x RJ9 (4P4C) headset port 1 x SV power port Dual USB ports (2.0 compliant) Bluetooth headset through BT40/BT41/BT51 Support Yealink Bluetooth headset BH71/BH71 Workstation/BH71 Workstation Pro/BH72/BH76/UH38 through BT51 DECT wireless headset (Yealink WH62 Portable/WH63 Portable) USB call recording through USB flash drive USB headset Expansion Module EXP55 Wireless Headset Adapter EHS40 USB/Bluetooth connectivity to Yealink CP900/CP700 speakerphone/wireless headset UH38, USB connectivity to Yealink wired headset UH34/UH36/UH37: Basic functions: answer/end, call mute Enhanced function: audio optimization, redial, call hold, volume synchronization, multiple call control
Management	 Configuration: browser/phone/auto-provision Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy Auto-provision with PnP Broadsoft device management Zero-sp-touch, TR-069 Phone lock for personal privacy protection Reset to factory, reboot Package tracing export, system log Support Yealink Device Management Platform (YDMP/YMCS)



	 Support SRTP protocol Support TLS1.3 HTTPS Certificate Management Configuration file encryption (AES256) Supported authentication mechanisms: MD5/SHA1/SHA224/-SHA256/SHA384/SHA512 OpenVPN, IEEE802.1X, L2TP VPN LLDP/CDP/DHCP VLAN ICE WPA2/WPA3
	 Secure Boot GARP (Generic Attribute Registration Protocol) Linux 6.1 version TEE hardware encryption solution
Other Physical Features	 Color: Classic Grey Wall mountable (optional) External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A output USB output currency: 5V 1A Power consumption (PSU): 1.8W-3.8W Power consumption (PoE): 2.3W-4.7W Dimension (W*D*H*T): 266 mm*226 mm*85 mm*54 mm Operating humidity: 10 - 95% Operating temperature: -10 to 45°C (+14 to 113°F) Storage temperature: -30 to +70°C (-22 to +158°F)



- Power Adapter (Optional) - Wall Mount Bracket (Optional) - Qty/CTN: 5 PCS - N.W/CTN: 6.99 kg - G.W/CTN: 7.702 kg - Giftbox size: XXmm*XXmm*XXmm - Carton Meas: XXmm* XXmm*XXmm
--